

HOFMANN®



Monty 3300EM Shown

Monty 3300/3300EM

TIRE CHANGER

Monty 3300/3300EM

TIRE CHANGER

The Hofmann 3300 and 3300EM high-performance tire changers are designed for high-volume tire shops, multi-bay repair shops and car dealerships to service standard, low-profile and run-flat tires on cars, SUV's and light trucks.

- Large wheel clamping range**
 Designed for performance tires with up to 24" in rim clamping diameter, the 3300/3300EM can change virtually any car, light truck or SUV tire.
- Dual rim clamping cylinders**
 Dual pneumatic clamping cylinders control all four clamping jaws. No damage from rim slippage in the jaws.
- Powerful two-position bead breaker**
 6000 lbs. of power at the bead shovel and a range up to 17" wide. The two stage pneumatic cylinder provides very precise power toggled with the foot pedal as it is needed. Both the stiffest and the softest sidewalls are a snap. No damage to tires while loosening the bead.
- Powerful tire inflation system**
 Foot pedal operated. Powerful air blast. Each movable jaw is precisely set to the exact position under the rim to seal the tire bead.
- Built to last**
 Heavy, solid 1/2 inch thick steel clamping table. Rugged steel reinforced chasis. All cylinders and valves cannot rust. A compressed air lubricator and regulator is onboard to keep valves and cylinders maintenance free.
- EasyMont Pro bead assist**
 This patented device holds the bead into the drop center allowing one operator to change low-profile, high performance and run-flat tires.

Hofmann manufactures a complete line of wheel service equipment.



Imaging & conventional alignment equipment



High performance wheel balancer with all automatic data entry.



Combination brake lathes for rotors, drums, and flywheels.

Specifications

Rim Clamping Diameter	10" - 24"
With optional adapters for	
Motorcycles/ATVs (EAA0329G53A)	10" - 24"
Outer clamping range	10" - 24"
Inner clamping range	12" - 24"
Maximum rim width	15"
Maximum wheel diameter	40"
Bead breaker range	2" to 17"
Compressed air supply	110 to 170 psi @ 5 CFM
Bead loosening power	6,000 lbs
Work area dimensions H x W x D	85" x 68" x 72"
Packing dimensions H x W x D	70" x 42" x 56"
Shipping weight	500 lbs
Power supply	115 V / 1 phase / 50 - 60 Hz / 15 amps
Drive motor	
Electric	U.S. Built 1 hp motor
Air	Available upon request

Optional Accessories

EasyMont bead assist device*	EAA0329G35A
Quick change bead head kit*	4028228
Protective insert for mount/demount head (1)	EAC0078G50A
Composite mount/demount head, complete	EAA0247G20A
Replacement Composite head only	ST0024335
Outside clamping jaw protectors (set 4)	ST4027645
Protective slide cover (1)	0029455
Protective cover for tire lever*	EAA0247G04A
Snap-in jaw protectors (Set of 4)	ST0022129
Protective cover for bead breaker shovel*	EAA0304G15A
Wave Tire Tool	EAA0304G14A
Rim Protector	
snap's onto rim, use w/Wave Tool*	ST4026853
Bead Clamp for performance wheels	EAA0247G70A
Bead Clamp for run-flat tires	ST4024078
Magic Bead Pusher, use w/EasyMont	EAA0304G92A
Bead Breaker Disc, use with hex bar	EAA0304G43A

*Standard with Monty 3300EM

HOFMANN[®]
USA

309 Exchange Avenue • Conway, AR 72032
 (800) 251-4500 • (501) 450-2662
 Fax (501) 450-2085 • www.hofmann-usa.com

HOFMANN[®]
Canada

6500 Millcreek Drive • Mississauga, ONT L5N 4G4
 (800) 267-2185
 Fax (905) 821-2073 • www.hofmann.ca
 E-mail: info@hofmann.ca