

# HOFMANN®



## **Monty 3550EM**

## **TIRE CHANGER**

# Monty 3550EM

## TIRE CHANGER

**Pneumatic tilt-tower tire changer specifically designed to change low-profile, high performance, and run-flat tires.**

- **Largest wheel clamping range**

Designed for tires up to 47" in outside diameter, and with a 30" rim diameter capacity, the 3550EM can change virtually any car or light truck tire.

- **Powerful bead breaker**

Double acting bead breaking cylinder delivers over 5,000 lbs. of force with complete control to avoid damaging rims. The 3550EM also has the ability to break the outer bead with the tire mounted on the turntable using the protective roller.

- **Pneumatically control bead head**

Push button controlled bead head pneumatically lowers and locks into position.

- **EasyMont Pro bead assist**

This patented device holds the bead into the drop center allowing one operator to change low-profile, high performance and run-flat tires.

- **Protect the most delicate wheels**

All metal parts have plastic protection providing no metal-to-metal contact when changing delicate rims.

- **Quick wheel protection change-over**

Plastic protection parts are quickly changed over from plastic to metal. Even the bead head is changed over from metal to plastic in a matter of seconds.

### Specifications

Outer clamping range	12" - 26"
With +4 jaws	16" - 30"
With optional adapters for Motorcycles/ATVs (EAA0329G53A)	8" - 23"
Inner clamping range	14" - 28"
Maximum rim width	17"
Maximum wheel diameter	47"
Bead breaking width	
Position 1	(2.5" to 12")
Position 2	(6" to 17")
Power supply	115 V / 1 phase / 50 - 60 Hz
Compressed air supply	100 to 170 psi @ 5 CFM
Bead loosening power	6,000 lbs
Work area dimensions H x W x D	85" x 68" x 72"
Packing dimensions H x W x D	70" x 42" x 56"
Shipping weight	975 lbs

**Hofmann manufactures a complete line of wheel service equipment.**



4-wheel alignment systems



High performance wheel balancer with all automatic data entry.



Combination brake lathes for rotors, drums, and flywheels.

**HOFMANN**<sup>®</sup>  
USA

309 Exchange Avenue • Conway, AR 72032  
(800) 251-4500 • (501) 450-1581  
Fax (501) 450-2085 • [www.hofmann-usa.com](http://www.hofmann-usa.com)

**HOFMANN**<sup>®</sup>  
Canada

6500 Millcreek Drive • Mississauga, ONT L5N 4G4  
(800) 267-2185 • (866) 812-5316  
Fax (905) 821-2073 • [www.hofmann.ca](http://www.hofmann.ca)  
E-mail: [info@hofmann.ca](mailto:info@hofmann.ca)