



COUNTERACT BALANCING BEADS

Application Chart Per Tire For Light and Medium Trucks

TIRE SIZE	1/2 TON	1 TON+
LIGHT TRUCK		
14"		
215/75R14	3 oz.	4 oz.
205/70R14	3 oz.	4 oz.
215/70R14	3 oz.	4 oz.
15"		
700R15		4 oz.
7.50R15		6 oz.
8.25R15		6 oz.
9R15		8 oz.
10R15		8 oz.
215/80R15	3 oz.	4 oz.
195/75R15	3 oz.	4 oz.
205/75R15	3 oz.	4 oz.
215/75R15	3 oz.	4 oz.
225/75R15	4 oz.	4 oz.
235/75R15	4 oz.	4 oz.
245/75R15	3 oz.	4 oz.
255/75R15	3 oz.	4 oz.
265/75R15	3 oz.	4 oz.
235/70R15	3 oz.	4 oz.
245/70R15	3 oz.	4 oz.
255/70R15	3 oz.	4 oz.
265/70R15	4 oz.	4 oz.
285/70R15	4 oz.	4 oz.
315/70R15	4 oz.	5 oz.
245/65R15	3 oz.	4 oz.
225/60R15	3 oz.	4 oz.
325/60R15	4 oz.	5 oz.
15.5"		
185/70R15.5	3 oz.	4 oz.
16"		
6.50R16		4 oz.
7.50R16		4 oz.
8.25R16		6 oz.
11R16		8 oz.
215/85R16	3 oz.	4 oz.
225/85R16	3 oz.	4 oz.
235/85R16	3 oz.	4 oz.
245/85R16	3 oz.	4 oz.
255/85R16	4 oz.	5 oz.
265/85R16	4 oz.	5 oz.
275/85R16	4 oz.	5 oz.
205/80R16	3 oz.	4 oz.
325/80R16	4 oz.	6 oz.
175/75R16	3 oz.	4 oz.
195/75R16	3 oz.	4 oz.
225/75R16	3 oz.	4 oz.
235/75R16	3 oz.	4 oz.
245/75R16	3 oz.	4 oz.
265/75R16	4 oz.	6 oz.
285/75R16	4 oz.	6 oz.
295/75R16	4 oz.	6 oz.
315/75R16	4 oz.	6 oz.
215/70R16	3 oz.	4 oz.
225/70R16	3 oz.	4 oz.
235/70R16	3 oz.	4 oz.
245/70R16	3 oz.	4 oz.
255/70R16	3 oz.	4 oz.

TIRE SIZE	1/2 TON	1 TON+
265/70R16	3 oz.	4 oz.
275/70R16	3 oz.	4 oz.
305/70R16	3 oz.	4 oz.
315/70R16	4 oz.	6 oz.
355/70R16	5 oz.	6 oz.
365/70R16	5 oz.	6 oz.
395/70R16	5 oz.	6 oz.
195/65R16	3 oz.	4 oz.
215/65R16	3 oz.	4 oz.
225/65R16	3 oz.	4 oz.
245/65R16	3 oz.	4 oz.
255/65R16	3 oz.	4 oz.
305/65R16	3 oz.	4 oz.
345/65R16	5 oz.	6 oz.
375/65R16	5 oz.	6 oz.
215/60R16	3 oz.	4 oz.
225/60R16	3 oz.	4 oz.
235/60R16	3 oz.	4 oz.
285/60R16	3 oz.	4 oz.
255/55R16	3 oz.	4 oz.
315/55R16	3 oz.	4 oz.
345/55R16	3 oz.	5 oz.
355/55R16	3 oz.	5 oz.
375/55R16	4 oz.	6 oz.
245/50R16	3 oz.	4 oz.
16.5"		
8R16.5	5 oz.	5 oz.
8.75R16.5	6 oz.	6 oz.
9.50R16.5	6 oz.	6 oz.
10R16.5	6 oz.	6 oz.
12R16.5	8 oz.	8 oz.
17"		
235/80R17	6 oz.	6 oz.
235/75R17	6 oz.	6 oz.
245/75R17	6 oz.	6 oz.
255/75R17	6 oz.	6 oz.
285/75R17	6 oz.	8 oz.
245/70R17	4 oz.	6 oz.
255/70R17	4 oz.	6 oz.
265/70R17	6 oz.	6 oz.
275/70R17	6 oz.	6 oz.
285/70R17	6 oz.	6 oz.
305/70R17	6 oz.	8 oz.
315/70R17	6 oz.	8 oz.
355/70R17	6 oz.	8 oz.
225/65R17	3 oz.	4 oz.
235/65R17	3 oz.	4 oz.
245/65R17	3 oz.	4 oz.
255/65R17	3 oz.	5 oz.
265/65R17	4 oz.	6 oz.
305/65R17	4 oz.	6 oz.
375/65R17	6 oz.	8 oz.
225/60R17	3 oz.	4 oz.
235/60R17	3 oz.	4 oz.
255/60R17	4 oz.	6 oz.
275/60R17	4 oz.	6 oz.
285/60R17	4 oz.	6 oz.
225/55R17	3 oz.	4 oz.

TIRE SIZE	1/2 TON	1 TON+
255/55R17	3 oz.	4 oz.
275/55R17	3 oz.	5 oz.
345/55R17	3 oz.	5 oz.
255/50R17	3 oz.	4 oz.
17.5"		
8R17.5	5 oz.	5 oz.
8.5R17.5	6 oz.	6 oz.
9R17.5	6 oz.	6 oz.
9.5R17.5	8 oz.	8 oz.
10R17.5	8 oz.	8 oz.
11R17.5	8 oz.	8 oz.
225/90R17.5	8 oz.	8 oz.
205/80R17.5	8 oz.	8 oz.
225/80R17.5	8 oz.	8 oz.
205/75R17.5	6 oz.	6 oz.
215/75R17.5	6 oz.	6 oz.
225/75R17.5	6 oz.	6 oz.
235/75R17.5	6 oz.	6 oz.
245/75R17.5	6 oz.	6 oz.
195/70R17.5	6 oz.	6 oz.
215/70R17.5	6 oz.	6 oz.
235/70R17.5	6 oz.	6 oz.
195/60R17.5	6 oz.	6 oz.
205/60R17.5	6 oz.	6 oz.
225/60R17.5	6 oz.	6 oz.
18"		
7.50R18	8 oz.	8 oz.
255/70R18	3 oz.	5 oz.
265/70R18	3 oz.	5 oz.
275/70R18	4 oz.	6 oz.
275/65R18	4 oz.	6 oz.
285/65R18	4 oz.	6 oz.
325/65R18	4 oz.	6 oz.
355/65R18	4 oz.	6 oz.
395/65R18	6 oz.	8 oz.
245/60R18	3 oz.	4 oz.
255/60R18	3 oz.	5 oz.
265/60R18	3 oz.	5 oz.
275/60R18	4 oz.	6 oz.
285/60R18	4 oz.	6 oz.
325/60R18	4 oz.	6 oz.
375/60R18	6 oz.	8 oz.
395/60R18	6 oz.	8 oz.
255/55R18	3 oz.	4 oz.
275/55R18	3 oz.	4 oz.
285/55R18	3 oz.	4 oz.
285/50R18	3 oz.	4 oz.
375/50R18	4 oz.	6 oz.
19"		
255/55R19	3 oz.	4 oz.
255/50R19	3 oz.	4 oz.
275/45R19	3 oz.	4 oz.
285/45R19	3 oz.	4 oz.
20"		
325/75R20	6 oz.	8 oz.
275/65R20	4 oz.	6 oz.
275/60R20	4 oz.	6 oz.
325/60R20	4 oz.	6 oz.

TIRE SIZE	1/2 TON	1 TON+
355/60R20	5 oz.	6 oz.
275/55R20	3 oz.	4 oz.
285/55R20	3 oz.	4 oz.
255/50R20	3 oz.	4 oz.
285/50R20	3 oz.	4 oz.
305/50R20	4 oz.	6 oz.
325/50R20	4 oz.	6 oz.
355/50R20	4 oz.	6 oz.
325/45R20	4 oz.	6 oz.
275/40R20	4 oz.	6 oz.
315/35R20	4 oz.	6 oz.
22"		
325/55R22	5 oz.	6 oz.
335/55R22	5 oz.	6 oz.
325/50R22	4 oz.	6 oz.
305/45R22	4 oz.	6 oz.
305/40R22	4 oz.	6 oz.
285/35R22	3 oz.	5 oz.
24"		
325/45R24	4 oz.	6 oz.



WHATEVER THE RIDE



WHATEVER THE ROAD

For Inquiries Call 1-800-572-8952
www.counteractbalancing.com

TIRE SIZE	SINGLE	DUAL
OFF-ROAD		
14"		
27/8.50R14	3 oz.	
15"		
29/9.50R15	4 oz.	
30/9.50R15	4 oz.	
33/9.50R15	6 oz.	
31/10.50R15	4 oz.	
33/10.50R15	6 oz.	
31/11.50R15	4 oz.	
32/11.50R15	6 oz.	
31/12.50R15	5 oz.	
32/12.50R15	6 oz.	
33/12.50R15	6 oz.	
35/12.50R15	6 oz.	
36/12.50R15	8 oz.	
37/12.50R15	8 oz.	
35/13.50R15	8 oz.	
31/14.50R15	6 oz.	
33/14.50R15	8 oz.	
36/14.50R15	10 oz.	
38/15.50R15	10 oz.	
33/16.50R15	8 oz.	
36/16.50R15	10 oz.	
40/17B15	10 oz.	
44/18.50B15	12 oz.	
16"		
32/9.50R16	6 oz.	
35/10.50R16	6 oz.	
31/12.50R16	6 oz.	
32/12.50R16	6 oz.	
33/12.50R16	6 oz.	
34/12.50R16	6 oz.	
35/12.50R16	6 oz.	
36/12.50R16	8 oz.	
37/12.50R16	8 oz.	
33/14.50R16	8 oz.	
36/14.50R16	10 oz.	
38/15.50R16	10 oz.	
16.5"		
31/10.50R16.5	4 oz.	
33/12.50R16.5	6 oz.	
35/12.50R16.5	6 oz.	
37/12.50R16.5	8 oz.	
33/14.50R16.5	8 oz.	
35/14.50R16.5	8 oz.	
38/15.50R16.5	10 oz.	
33/16.50R16.5	8 oz.	
36/16.50R16.5	10 oz.	
40/17B16.5	10 oz.	
44/18.50B16.5	12 oz.	

TIRE SIZE	SINGLE	DUAL
17"		
33/12.50R17	6 oz.	
35/12.50R17	6 oz.	
37/12.50R17	8 oz.	
37/13.50R17	10 oz.	
40/13.50R17	10 oz.	
18"		
35/12.50R18	6 oz.	
37/12.50R18	8 oz.	
20"		
35/12.50R20	6 oz.	
37/12.50R20	8 oz.	
MED. TRUCK		
19.5"		
8R19.5	6 oz.	8 oz.
9R19.5	6 oz.	8 oz.
18R19.5	14 oz.	
280/75R19.5	8 oz.	
285/75R19.5	8 oz.	
225/70R19.5	6 oz.	8 oz.
245/70R19.5	6 oz.	8 oz.
265/70R19.5	8 oz.	8 oz.
275/70R19.5	8 oz.	10 oz.
285/70R19.5	8 oz.	10 oz.
305/70R19.5	10 oz.	12 oz.
385/65R19.5	12 oz.	14 oz.
445/65R19.5	14 oz.	
20"		
7.50R20	8 oz.	10 oz.
8.25R20	8 oz.	10 oz.
9.00R20	10 oz.	12 oz.
10.00R20	10 oz.	12 oz.
11.00R20	12 oz.	14 oz.
12.00R20	12 oz.	14 oz.
12.5R20	12 oz.	14 oz.
13/80R20	12 oz.	14 oz.
14/80R20	12 oz.	14 oz.
14.00R20	16 oz.	16 oz.
365/80R20	16 oz.	16 oz.
395/80R20	16 oz.	16 oz.
20.5"		
525/65R20.5	20 oz.	
615/65R20.5	22 oz.	
22"		
10.00R22	12 oz.	
11.00R22	12 oz.	
22.5"		
9R22.5	8 oz.	10 oz.
10R22.5	8 oz.	10 oz.
11R22.5	10 oz.	12 oz.
12R22.5	12 oz.	14 oz.

TIRE SIZE	SINGLE	DUAL
13R22.5	12 oz.	
15R22.5	12 oz.	
16R22.5	14 oz.	
16.5R22.5	14 oz.	
18R22.5	16 oz.	
235/80R22.5	6 oz.	8 oz.
255/80R22.5	8 oz.	10 oz.
275/80R22.5	10 oz.	12 oz.
295/80R22.5	12 oz.	14 oz.
315/80R22.5	14 oz.	
365/80R22.5	14 oz.	
245/75R22.5	8 oz.	10 oz.
265/75R22.5	8 oz.	10 oz.
285/75R22.5	10 oz.	12 oz.
295/75R22.5	10 oz.	12 oz.
315/75R22.5	12 oz.	
345/75R22.5	12 oz.	
350/75R22.5	14 oz.	
235/70R22.5	6 oz.	8 oz.
255/70R22.5	8 oz.	10 oz.
11/70R22.5	8 oz.	10 oz.
265/70R22.5	8 oz.	10 oz.
275/70R22.5	10 oz.	12 oz.
305/70R22.5	10 oz.	12 oz.
315/70R22.5	10 oz.	12 oz.
365/70R22.5	12 oz.	
365/65R22.5	12 oz.	
385/65R22.5	12 oz.	
425/65R22.5	14 oz.	
445/65R22.5	16 oz.	
285/60R22.5	10 oz.	
295/60R22.5	10 oz.	
305/60R22.5	10 oz.	
315/60R22.5	10 oz.	
385/55R22.5	12 oz.	
455/55R22.5	16 oz.	
275/50R22.5	10 oz.	12 oz.
445/50R22.5	16 oz.	
24"		
11.00R24	14 oz.	
12.00R24	14 oz.	
14.00R24	16 oz.	
445/70R24	16 oz.	
495/70R24	16 oz.	
24.5"		
11R24.5	10 oz.	12 oz.
12R24.5	14 oz.	14 oz.
285/75R24.5	10 oz.	12 oz.
305/75R24.5	10 oz.	12 oz.
315/75R24.5	10 oz.	12 oz.
275/80R24.5	10 oz.	12 oz.
295/80R24.5	10 oz.	12 oz.

For Inquiries Call 1-800-572-8952

To achieve maximum results it is important to use the proper package size for each tire. As a rule of thumb, the amount of Counteract Balancing Beads required per tire is based on one ounce per thirteen pounds of tire. If you are not using an applicator and pouring the contents of the bag directly into the tire it is imperative that none of the contents of the bag ends up on the bead seating area of the tire and rim. If you are using our new throw in bags, open & discard outside bag only & throw clear inner bag containing CBB directly inside tire cavity. Counteract disclaims any responsibility for air loss or tire damage due to improper installation or air check. In order to reduce the possibility of valve leaks, the use of a long valve core or valve core filter and a metal valve cap is recommended.